

B25

APPLICATIONS

- medium to large size touring
- low frequency extension for A8, A12 and C15
- medium to large installations

FEATURES

- two high excursion 15" neodymium woofers
- unique folded- horn design
- fibre class strengthened birch plywood enclosure
- heavy-duty wheels and 8 ABS handles

B25 - SPECIFICATIONS

Frequency Response (-10 dB): 40 Hz – 200 Hz
Frequency Response (column of 4 units): 33 Hz – 200 Hz
Horizontal Coverage (-6 dB): 360 degrees
Vertical Coverage (-6 dB): 360 degrees
Max SPL: 132/138 dB (free space)
Sensitivity, 1w/1m: 102 dB (free space)
Impedance: 4 ohms
Crossover: 80 Hz – 200 Hz active
Power handling: 1000 W cont, 4000 W peak
Recommended HP-filter: 33 Hz, 12 dB/octave

Drivers

LF: (2) x 15" neodymium magnet cone driver, 4" voice coil

Enclosure

Enclosure material: Fibre class strengthened birch plywood, textured black paint finish
Grille: Cold rolled steel grille, textured black paint finish
Connectors: (2) x NL4, +/-1: Input, +/-2: Linked
Dimensions: 990 mm x 570 mm x 985 mm
Weight: 84 kg

